

Light Measurement Report

Print date: 8-5-2025

Measurement date and time: 7-5-2025 15:24:29 – Measurement no. VFR-250507-1135-MS

Measurement tracking No. and Link: [VT250507-002774](#)

Operator:



Laboratory and Equipment

Laboratory Owner and Location

Goniospectrometer System and Type

Sensor Name, Calibr. Date and Serial No.

Spectrometer Manufacturer and Model

Viso Systems, Copenhagen V, Denmark

LabSpion – Type C, horizontal

LabSensor Model2 – 11-1-2024 – 3130191315

Ibsen Photonics, Denmark – Freedom VIS (Custom Viso)

Measurement Conditions

Number of C-planes and Resolution

γ (gamma)-Resolution

Test Distance

Input Power, Power and Displ. Factors

Input RMS Voltage and Current

Frequency of Input Power

Warm-up Time and Variation

72 planes – 5°

5°

2,00 m

28,3 W – PF 0,96 – DPF 0,97

230 V – 0,129 A

50 Hz

Lamp stabilized in 17 min 19 sec – 2,0%

Tested Light Source

Product Name

Item No. and Manufacturer

Product Description (line 1)

800970-3000K

800970-3000K – Dutchfulfillment

3-FASE RAILSPOT ERRIAP 30W CRI>95 WIT

Main Light Measurement Results

Output – Total Lumen (Up% / Down%)

Efficiency

Peak Intensity and Beam Angle

Correlated Color Temperature, Target/Measured

Color Rendering Index

Color Rendering TM30-18

Color Shift, CIE duv and MacAdam Steps

Flicker

2863 lm – 0,01% / 99,99%

101 lm/W

11067 cd – 18,4°



CCT = 3000 K / 3089 K

CRI 98,3

R_f 94,4 – R_g 100,5

Duv 0,0006 – SDCM 3,0

SVM 0,01 – PstLM 0,02



Light Measurement Report

Print date: 8-5-2025

Measurement date and time: 7-5-2025 15:24:29 – Measurement no. VFR-250507-1135-MS


Measurement tracking No. and Link: [VT250507-002774](#)

Operator:



Luminous Intensity diagram

Unit: 0-100% of peak intensity



Main Values

Output (total Lumen)	2863 lm
Lumen Up% / Down%	0,01% / 99,99%
Peak Intensity	11067 cd
Beam Angle (50%)	18,4°
Beam Angle (90%)	18,4°
Beam Angle (10%)	18,4°

Cut-off Angle

Average 2,5%	93,1°
--------------	-------

Field Angle

Average 10%	58,3°
-------------	-------


Intensity Ratio

In 120° cone	99,1%
In 90° cone	95,2%

C000-C180

C090-C270

Linear distribution diagram - Intensity (candela) vs γ-angle




Light Measurement Report


Print date: 8-5-2025
Measurement date and time: 7-5-2025 15:24:29 – Measurement no. VFR-250507-1135-MS
Measurement tracking No. and Link: [VT250507-002774](#)
Operator:



Iso-intensity Diagram (Iso-candela)



Iso-illuminance Diagram (Iso-lux)



Light Measurement Report

Print date: 8-5-2025

Measurement date and time: 7-5-2025 15:24:29 – Measurement no. VFR-250507-1135-MS

Measurement tracking No. and Link: [VT250507-002774](#)

Operator:




Color details


Correlated Color Temperature, Target CCT = 3000 K
Correlated Color Temperature, Measured CCT = 3089 K
Color Rendering Index CRI 98,3
Color Rendering Index, R9 (red component) R9 = 95,9
Color Rendering TM30-18 R_f 94,4 – R_g 100,5
Color Quality Scale CQS = 95,8

MacAdam Steps
Color coordinates CIE 1931 (x;y) = (0,437;0,404)
Color coordinate CIEs 1960 (u;v) = (0,251;0,348)
Color deviation from BBL Duv = 0,0006
Color coordinate CIEs 1976 (CIELUV) (u';v') = (0,251;0,521)


CIE 1931



CIE 1931 – zoomed on Planckian locus




Color Rendering Index per reference color (CIE 1995)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
98,3	99,9	96,0	98,2	98,9	97,9	99,1	98,6	95,9	97,8	95,8	83,4	98,6	96,7	98,5


TM30-18 R_f -values per hue bin




TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
96,3	97,9	96,7	95,0	93,7	97,2	93,5	97,3	94,1	91,6	91,6	92,4	95,4	93,2	92,4	90,2

Spectral power distribution (SPD) / W/nm – 0-100%



Color Quality Scale by reference color



CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
93,4	96,8	92,9	93,7	96,4	98,3	96,7	98,3	97,1	97,2	97,1	96,7	96,9	97,0	95,7

Light Measurement Report

Print date: 8-5-2025


Measurement date and time: 7-5-2025 15:24:29 – Measurement no. VFR-250507-1135-MS

Measurement tracking No. and Link: [VT250507-002774](#)

Operator:



Beam Details



Beam intensities from 1 – 20 m

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	m
3,3	6,6	9,8	13,1	16,4	19,7	23	26,2	29,5	32,8	36,1	39,4	42,7	45,9	49,2	52,5	55,8	59,1	62,3	65,6	ft
11067	2767	1230	692	443	307	226	173	137	111	91	77	65	56	49	43	38	34	31	28	lux
1028,1	257	114,2	64,3	41,1	28,6	21	16,1	12,7	10,3	8,5	7,1	6,1	5,2	4,6	4	3,6	3,2	2,8	2,6	fc

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
11,1K	11,0K	9,6K	8,1K	6,6K	4,8K	3,1K	2,5K	1,8K	1,4K	1,3K	1,2K	1,2K	1,1K	1,1K	1,1K	1,1K	1,0K	1,0K	0,9K	cd
100%	100%	87%	74%	59%	44%	28%	22%	16%	13%	12%	11%	11%	10%	10%	10%	10%	9%	9%	8%	of 0°val

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
11,1K	11,0K	9,6K	8,1K	6,6K	4,8K	3,1K	2,5K	1,8K	1,4K	1,3K	1,2K	1,2K	1,1K	1,1K	1,1K	1,1K	1,0K	1,0K	0,9K	cd
100%	100%	87%	74%	59%	44%	28%	22%	16%	13%	12%	11%	11%	10%	10%	10%	10%	9%	9%	8%	of 0°val

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
11,1K	11,0K	9,6K	8,1K	6,6K	4,8K	3,1K	2,5K	1,8K	1,4K	1,3K	1,2K	1,2K	1,1K	1,1K	1,1K	1,1K	1,0K	1,0K	0,9K	cd
100%	100%	87%	74%	59%	44%	28%	22%	16%	13%	12%	11%	11%	10%	10%	10%	10%	9%	9%	8%	of 0°val

Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
11,1K	11,0K	9,6K	8,1K	6,6K	4,8K	3,1K	2,5K	1,8K	1,4K	1,3K	1,2K	1,2K	1,1K	1,1K	1,1K	1,1K	1,0K	1,0K	0,9K	cd
100%	100%	87%	74%	59%	44%	28%	22%	16%	13%	12%	11%	11%	10%	10%	10%	10%	9%	9%	8%	of 0°val

Light Measurement Report

Print date: 8-5-2025

Measurement date and time: 7-5-2025 15:24:29 – Measurement no. VFR-250507-1135-MS

Measurement tracking No. and Link: [VT250507-002774](#)

Operator:



Light Planning – UGR table

Uncorrected, comprehensive UGR table according to 117-1995

Reflectances											
	ρ Ceiling	70	70	50	50	30	70	70	50	50	30
	ρ Walls	50	30	50	30	30	50	30	50	30	30
	ρ Floor	20	20	20	20	20	20	20	20	20	20
Room size		Viewed Crosswise					Viewed Endwise				
H = mounting height above eye level		(Viewing direction orthogonal to lamp length axis)					(Viewing direction parallel to lamp length axis)				
X	Y										
2H	2H	22,0	22,6	22,1	22,9	23,1	22,0	22,6	22,1	22,9	23,1
	3H	21,7	22,5	22,1	22,7	22,9	21,7	22,5	22,1	22,7	22,9
	4H	21,7	22,4	22,0	22,6	22,8	21,7	22,4	22,0	22,6	22,8
	6H	21,7	22,3	22,0	22,6	22,9	21,7	22,3	22,0	22,6	22,9
	8H	21,6	22,2	21,9	22,5	22,9	21,6	22,2	21,9	22,5	22,9
	12H	21,6	22,1	21,9	22,5	22,9	21,6	22,1	21,9	22,5	22,9
4H	2H	21,6	22,4	22,0	22,6	22,8	21,6	22,4	22,0	22,6	22,8
	3H	21,6	22,1	21,9	22,5	22,9	21,6	22,1	21,9	22,5	22,9
	4H	21,4	21,9	21,8	22,4	22,9	21,4	21,9	21,8	22,4	22,9
	6H	21,4	21,9	21,9	22,2	22,6	21,4	21,9	21,9	22,2	22,6
	8H	21,3	21,8	21,8	22,2	22,5	21,3	21,8	21,8	22,2	22,5
	12H	21,3	21,6	21,8	22,1	22,5	21,3	21,6	21,8	22,1	22,5
8H	4H	21,3	21,8	21,8	22,1	22,5	21,3	21,8	21,8	22,1	22,5
	6H	21,3	21,6	21,8	22,1	22,6	21,3	21,6	21,8	22,1	22,6
	8H	21,3	21,5	21,8	22,0	22,7	21,3	21,5	21,8	22,0	22,7
	12H	21,2	21,4	21,8	21,9	22,5	21,2	21,4	21,8	21,9	22,5
12H	4H	21,2	21,6	21,7	22,0	22,5	21,2	21,6	21,7	22,0	22,5
	6H	21,3	21,5	21,8	22,0	22,7	21,3	21,5	21,8	22,0	22,7
	8H	21,2	21,4	21,8	21,9	22,5	21,2	21,4	21,8	21,9	22,5
Variations with the observer position for the luminaire spacings, S:											
S = 1.0H		2,6 / -11,1					2,6 / -11,1				
S = 1.5H		4,9 / -12,1					4,9 / -12,1				
S = 2.0H		6,8 / -12,4					6,8 / -12,4				

Coefficients of Utilization

Ceiling reflectance	80			70			50			30			10			0		
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR		(RCR: Room Cavity Ratio)			Room Values are expressed as percentage of Lumen delivered to the task surface													
0	119	119	119	119	116	116	116	111	111	111	106	106	106	102	102	102	100	
1	114	111	109	106	111	109	107	105	105	103	101	101	100	98	98	97	96	94
2	108	104	100	96	106	102	98	95	99	96	93	96	93	91	93	91	89	88
3	103	97	92	88	101	96	91	88	93	89	86	90	87	85	88	86	84	82
4	98	91	86	82	96	90	85	81	88	83	80	86	82	79	84	81	78	77
5	94	86	80	76	92	85	80	76	83	78	75	81	77	74	80	76	74	72
6	89	81	75	71	88	80	75	71	79	74	70	77	73	70	76	72	69	68
7	85	77	71	67	84	76	71	67	75	70	66	74	69	66	72	69	66	64
8	82	73	67	63	81	72	67	63	71	66	63	70	66	63	69	65	62	61
9	78	69	64	60	77	69	64	60	68	63	60	67	63	60	66	62	59	58
10	75	66	61	57	74	66	61	57	65	60	57	64	60	57	64	60	57	56


Light Measurement Report

Print date: 8-5-2025
Measurement date and time: 7-5-2025 15:24:29 – Measurement no. VFR-250507-1135-MS
Measurement tracking No. and Link: [VT250507-002774](#)
Operator:



Luminaire budgetary diagram

Uncorrected, comprehensive UGR table according to 117-1995
LAMPS (number of lamps)



Conditions

H = Room height	Flux = 2863 lm	p(%)		
H _{down} = Lamp distance from ceiling =	0.00 m	Line type	Ceiling reflectance	Wall reflectance
H _{work} = Work area height from floor =	0.00 m	-----	70	50
E _{work} = Average lux on work area =	100 lx	-----	50	30
				Floor reflectance
				20

Zonal Lumen Summary

0°-10°	10°-20°	20°-30°	30°-40°	40°-50°	50°-60°	60°-70°	70°-80°	80°-90°
738 lm	584 lm	533 lm	628 lm	330 lm	22,5 lm	12,3 lm	10,9 lm	3,76 lm
90°-100°	100°-110°	110°-120°	120°-130°	130°-140°	140°-150°	150°-160°	160°-170°	170°-180°
0,007 lm	0,000 lm	0,000 lm	0,000 lm	0,000 lm	0,000 lm	0,028 lm	0,135 lm	0,026 lm

Light Measurement Report

Print date: 8-5-2025

Measurement date and time: 7-5-2025 15:24:29 – Measurement no. VFR-250507-1135-MS

Measurement tracking No. and Link: [VT250507-002774](#)

Operator:



Outdoor Light Planning

Lumen per Zone

Zone (γ)	Lumen	% Total
0-10°	738 lm	25,8%
10-20°	584 lm	20,4%
20-30°	533 lm	18,6%
30-40°	628 lm	21,9%
40-50°	330 lm	11,5%
50-60°	23 lm	0,8%
60-70°	12 lm	0,4%
70-80°	11 lm	0,4%
80-90°	4 lm	0,1%
90-100°	0 lm	0,0%
100-110°	0 lm	0,0%
110-120°	0 lm	0,0%
120-130°	0 lm	0,0%
130-140°	0 lm	0,0%
140-150°	0 lm	0,0%
150-160°	0 lm	0,0%
160-170°	0 lm	0,0%
170-180°	0 lm	0,0%
Total	2863 lm	100,0%

Intensity peaks

Max intensity	11067 cd
Intensity, 90°	0 cd
Intensity, 0°	11067 cd

Zonal Lumen summary

Zone (γ)	Lumen	% Total
0-30°	1855 lm	64,8%
0-40°	2483 lm	86,7%
0-60°	2835 lm	99,1%
60-90°	27 lm	0,9%
70-100°	15 lm	0,5%
90-120°	0 lm	0,0%
0-90°	2862 lm	100,0%
90-180°	0 lm	0,0%
0-180°	2863 lm	100,0%

BUG rating

	Lumen	% Total
Forward light		
Low(0-30°)	930 lm	32,5%
Medium(30-60°)	488 lm	17,1%
High(60-80°)	11 lm	0,4%
Very high(80-90°)	2 lm	0,1%
Back light		
Low(0-30°)	930 lm	32,5%
Medium(30-60°)	488 lm	17,1%
High(60-80°)	11 lm	0,4%
Very high(80-90°)	2 lm	0,1%


Uplight

Low(90-100°)	0 lm	0,0%
High(100-180°)	0 lm	0,0%

IESNA TM-15-07

Luminaire Classification System For Outdoor Luminaires

BUG rating B2 U0 G0



Light Measurement Report

Print date: 8-5-2025
Measurement date and time: 7-5-2025 15:24:29 – Measurement no. VFR-250507-1135-MS
Measurement tracking No. and Link: [VT250507-002774](#)
Operator:




Power Details


Input Power

Power feed to light source	28,3 W
Frequency of input power	50 Hz
RMS Input voltage feed, V_{RMS}	230 V
RMS Input current feed, I_{RMS}	0,129 A
Volt-Ampere or apparent power = $V_{RMS} * I_{RMS}$	29,66 VA
Displacement factor of AC power feed	0,97
Power factor of AC current feed	0,96
Total harmonic distortion of the current	15,91%
Total harmonic distortion of the voltage	0,07%

Input Power Curve



Efficiency



Stabilization Details

Warmup Conditions

Stable period	15 min
Stable change max	2,0%
Minimum time	15 min

Color Temperature Change

CCT start	3015 K
CCT shift	-15 K
CCT end	3000 K


Warmup Result

Total warmup time	Lamp stabilized in 17 min 19 sec
Warmup variation	-2,7%

Output Change

Output start	2940 lm
Output change	-77 lm
Output end	2863 lm

Stabilization Curve



Light Measurement Report


Print date: 8-5-2025
Measurement date and time: 7-5-2025 15:24:29 – Measurement no. VFR-250507-1135-MS
Measurement tracking No. and Link: [VT250507-002774](#)
Operator:



Flicker /TLA details

Flicker Meter Type	Viso Systems LabFlicker	Measurement time	
Frequency of input power	50 Hz	PstLM	180 sec
Flicker/TLA sample rate	20000 samples/s	All other indices	1,2 sec
Flicker indices according to Illuminating Engineering Society (IES)		Flicker indices according to California Energy Commission (CEC) 2016b	
Flicker frequency	101,01 Hz	JA8/10 40 Hz	0,03 %
Percent Flicker	0,31 %	JA8/10 90 Hz	0,03 %
Flicker index	0	JA8/10 200 Hz	0,28 %
TLA indices (re IEC TR 61547-1, IEC 61000-3-3 and IEC 61000-4-15)		JA8/10 400 Hz	0,28 %
PstLM value (F < 80 Hz)	0,02	JA8/10 1000 Hz	0,3 %
SVM value (80 < F < 2000 Hz)	0,01	Flicker indices according to Lighting Research Center (2015)	
		Perception metric, Assist Mp	0,01

Flicker frame (frame of one flicker period in time domain)



Flicker FFT (flicker curve in frequency domain)



IEEE 1789 Frequency/modulation plot

